



MORE PEOPLE BUY AND  
FLY CESSNA AIRPLANES  
THAN ANY OTHER MAKE

1969

WORLD'S LARGEST PRO-  
DUCER OF GENERAL  
AVIATION AIRCRAFT  
SINCE 1956

G-AZLV

MODEL  
172  
AND  
SKYHAWK

OWNER'S  
MANUAL

## PERFORMANCE - SPECIFICATIONS

	Model 172*	Skyhawk*
<b>GROSS WEIGHT</b> . . . . .	2300 lbs	2300 lbs
<b>SPEED:</b>		
Top Speed at Sea Level . . . . .	139 mph	140 mph
Cruise, 75% Power at 9000 ft . . . . .	131 mph	132 mph
<b>RANGE:</b>		
Cruise, 75% Power at 9000 ft . . . . .	615 miles	620 miles
38 Gal. No Reserve	4.7 hours	4.7 hours
131 mph		132 mph
Cruise, 75% Power at 9000 ft . . . . .	775 miles	780 miles
48 Gal. No Reserve	5.9 hours	5.9 hours
131 mph		132 mph
Optimum Range at 10,000 ft . . . . .	640 miles	655 miles
38 Gal. No Reserve	5.5 hours	5.5 hours
117 mph		118 mph
Optimum Range at 10,000 ft . . . . .	820 miles	830 miles
48 Gal. No Reserve	7.0 hours	7.0 hours
117 mph		118 mph
<b>RATE OF CLIMB AT SEA LEVEL</b> . . . . .	645 fpm	645 fpm
<b>SERVICE CEILING</b> . . . . .	13,100 ft	13,100 ft
<b>TAKE-OFF:</b>		
Ground Run . . . . .	865 ft	865 ft
Total Distance Over 50-Foot Obstacle. . . . .	1525 ft	1525 ft
<b>LANDING:</b>		
Landing Roll . . . . .	520 ft	520 ft
Total Distance Over 50-Foot Obstacle. . . . .	1250 ft	1250 ft
<b>EMPTY WEIGHT (Approximate)</b> . . . . .	1245 lbs	1315 lbs
<b>BAGGAGE</b> . . . . .	120 lbs	120 lbs
<b>WING LOADING: Pounds/Sq Foot</b> . . . . .	13.2	13.2
<b>POWER LOADING: Pounds/HP</b> . . . . .	15.3	15.3
<b>FUEL CAPACITY: Total</b>		
Standard Tanks . . . . .	42 gal.	42 gal.
Optional Long Range Tanks . . . . .	52 gal.	52 gal.
<b>OIL CAPACITY: Total</b> . . . . .	8 qts	8 qts
<b>PROPELLER: Fixed Pitch (Diameter)</b> . . . . .	76 inches	76 inches
<b>ENGINE:</b>		
Lycoming Engine		
150 rated HP at 2700 RPM. . . . .	O-320-E2D	O-320-E2D

\*This manual covers operation of the Model 172/Skyhawk which is certificated as Model 172K under FAA Type Certificate No. 3A12.

COPYRIGHT © 1985

Cessna Aircraft Company  
Wichita, Kansas USA

D625-13-RPC-400-3/85

## CONGRATULATIONS . . . . .

Welcome to the ranks of Cessna owners! Your Cessna has been designed and constructed to give you the most in performance, economy, and comfort. It is our desire that you will find flying it, either for business or pleasure, a pleasant and profitable experience.

This Owner's Manual has been prepared as a guide to help you get the most pleasure and utility from your Model 172/Skyhawk. It contains information about your Cessna's equipment, operating procedures, and performance; and suggestions for its servicing and care. We urge you to read it from cover to cover, and to refer to it frequently.

Our interest in your flying pleasure has not ceased with your purchase of a Cessna. World-wide, the Cessna Dealer Organization backed by the Cessna Service Department stands ready to serve you. The following services are offered by most Cessna Dealers:

**FACTORY TRAINED PERSONNEL** to provide you with courteous expert service.


**FACTORY APPROVED SERVICE EQUIPMENT** to provide you with the most efficient and accurate workmanship possible.

**A STOCK OF GENUINE CESSNA SERVICE PARTS** on hand when you need them.

**THE LATEST AUTHORITATIVE INFORMATION FOR SERVICING CESSNA AIRPLANES**, since Cessna Dealers have all of the Service Manuals and Parts Catalogs, kept current by Service Letters and Service News Letters, published by Cessna Aircraft Company.

We urge all Cessna owners to use the Cessna Dealer Organization to the fullest.

A current Cessna Dealer Directory accompanies your new airplane. The Directory is revised frequently, and a current copy can be obtained from your Cessna Dealer. Make your Directory one of your cross-country flight planning aids; a warm welcome awaits you at every Cessna Dealer.



## TABLE OF CONTENTS

	Page=
SECTION I - OPERATING CHECK LIST.....	1-1
SECTION II - DESCRIPTION AND OPERATING DETAILS .....	2-1
SECTION III - OPERATING LIMITATIONS.....	3-1
SECTION IV - CARE OF THE AIRPLANE .....	4-1
OWNER FOLLOW-UP SYSTEM .....	4-10
SECTION V - OPERATIONAL DATA .....	5-1
SECTION VI - OPTIONAL SYSTEMS.....	6-1
ALPHABETICAL INDEX .....	Index-1

"This is the Flight Manual which forms part of the Certificate of Airworthiness for aircraft **G-AZLV**"



This manual describes the operation and performance of both the Cessna Model 172 and Skyhawk. Equipment described as "Optional" denotes that the subject equipment is optional on the Model 172. Much of this equipment is standard on the Skyhawk model.

CIVIL AVIATION AUTHORITY

CONSTRUCTORS NO **172-57908**

REGISTRATION MARKS **G-AZLV**



"This is the manual which forms part of Certificate of Airworthiness Number....."

# Section I

## OPERATING CHECK LIST

One of the first steps in obtaining the utmost performance, service, and flying enjoyment from your Cessna is to familiarize yourself with your airplane's equipment, systems, and controls. This can best be done by reviewing this equipment while sitting in the airplane. Those items whose function and operation are not obvious are covered in Section II.

Section I lists, in Pilot's Check List form, the steps necessary to operate your airplane efficiently and safely. It is not a check list in its true form as it is considerably longer, but it does cover briefly all of the points that you should know for a typical flight.

The flight and operational characteristics of your airplane are normal in all respects. There are no "unconventional" characteristics or operations that need to be mastered. All controls respond in the normal way within the entire range of operation. All airspeeds mentioned in Sections I and II are indicated airspeeds. Corresponding calibrated airspeed may be obtained from the Airspeed Correction Table in Section V.


### BEFORE ENTERING THE AIRPLANE.

- (1) Make an exterior inspection in accordance with figure 1-1.

### BEFORE STARTING THE ENGINE.

- (1) Seats and Seat Belts -- Adjust and lock.
- (2) Fuel Selector -- "BOTH."
- (3) Brakes -- Test and set.
- (4) Radios and Flashing Beacon -- "OFF."

## EXTERIOR INSPECTION



### Note

Visually check fuel filler caps, inspection plates, and general aircraft condition during walk-around inspection.

If night flight is planned, check operation of all lights, and make sure a flashlight is available.

- Turn on master switch and check fuel quantity indicators, then turn master switch off.
    - Check ignition switch "OFF".
    - Check fuel selector valve handle on "BOTH".
    - Remove control wheel lock.
    - Check baggage door for security.
  - Remove rudder gust lock, if installed.
    - Disconnect tail tie-down.
  - Disconnect wing tie-down.
    - Check main wheel tire for proper inflation.
  - Check oil level. Do not operate with less than six quarts. Fill for extended flight.
    - Before first flight of day and after each refueling, pull out strainer drain knob for about four seconds to clear fuel strainer of possible water and sediment. Check strainer drain closed. If water is observed, there is a possibility that the fuel tank sumps contain water. Thus, the fuel tank sump drain plugs and fuel line drain plug should be removed to check for the presence of water.
  - Remove pitot tube cover, if installed, and check pitot tube opening for stoppage.
    - Check fuel tank vent opening for stoppage.
    - Check stall warning vent opening for stoppage.
  - Same as **(3)**
- Check propeller and spinner for nicks and security.
  - Check nose wheel strut and tire for proper inflation.
  - Disconnect tie-down rope.
  - Inspect airspeed static source hole on side of fuselage for stoppage (left side only).

Figure 1-1.

CAA Approved change sheet & supplements for Embodiment in this Manual

Date	Origin And Title	Approval Authority	Position in Manual
21-5-08	CAA SUPP / ISSUE /	CAA	END OF MANUAL
---	AIRWORTHINESS NOTICE 88	CAA	---
---	WEIGHT & BALANCE	CAA	PAGE 3-5

## STARTING THE ENGINE.

- (1) Mixture -- Rich.
- (2) Carburetor Heat -- Cold.
- (3) Primer -- 2 - 6 strokes (as required; none if engine is warm).  
Close and lock primer.
- (4) Throttle -- Open 1/8".
- (5) Master Switch -- "ON."
- (6) Propeller Area -- Clear.
- (7) Ignition Switch -- "START" (release when engine starts).
- (8) Oil Pressure -- Check.

## BEFORE TAKE-OFF.

- (1) Parking Brake -- Set.
- (2) Cabin Doors -- Closed and locked.
- (3) Flight Controls -- Check.
- (4) Trim Tab -- "TAKE-OFF" setting.
- (5) Throttle Setting -- 1700 RPM.
- (6) Engine Instruments and Ammeter -- Check.
- (7) Suction Gage -- Check (4.6 to 5.4 inches of mercury).
- (8) Carburetor Heat -- Check operation.
- (9) Magnetos -- Check (RPM drop should not exceed 125 RPM on either magneto or 50 RPM differential between magnetos).
- (10) Flight Instruments and Radios -- Set.
- (11) Optional Autopilot or Wing Leveler -- Off.

## TAKE-OFF.

### NORMAL TAKE-OFF.

- (1) Wing Flaps -- 0°.
- (2) Carburetor Heat -- Cold.
- (3) Power -- Full throttle.
- (4) Elevator Control -- Lift nosewheel at 60 MPH.
- (5) Climb Speed -- 85 MPH.

### MAXIMUM PERFORMANCE TAKE-OFF.

- (1) Wing Flaps -- 0°.
- (2) Carburetor Heat -- Cold.

- (3) Brakes -- Apply.
- (4) Power -- Full throttle.
- (5) Brakes -- Release.
- (6) Airplane Attitude -- Slightly tail low.
- (7) Climb Speed -- 68 MPH until all obstacles are cleared.

## CLIMB.

### NORMAL CLIMB.

- (1) Airspeed -- 80 to 90 MPH.
- (2) Power -- Full throttle.
- (3) Mixture -- Full rich (mixture may be leaned above 5000 feet).

### MAXIMUM PERFORMANCE CLIMB.

- (1) Airspeed -- 82 MPH at sea level to 79 MPH at 10,000 feet.
- (2) Power -- Full throttle.
- (3) Mixture -- Full rich (mixture may be leaned above 5000 feet).

## CRUISING.

- (1) Power 2200 to 2700 RPM.

### NOTE

Maximum cruise RPM varies with altitude. For details, refer to Section V.

- (2) Trim Tab -- Adjust.
- (3) Mixture -- Lean for maximum RPM.

## LET-DOWN.

- (1) Mixture -- Rich.
- (2) Power -- As desired.
- (3) Carburetor Heat -- As required to prevent carburetor icing.

## BEFORE LANDING.

- (1) Fuel Selector -- "BOTH."
- (2) Mixture -- Rich.
- (3) Carburetor Heat -- Apply full heat before closing throttle.
- (4) Wing Flaps -- As desired.
- (5) Airspeed -- 70 to 80 MPH (flaps up), 65 to 75 MPH (flaps down).

## BALKED LANDING (GO-AROUND).

- (1) Power -- Full throttle.
- (2) Carburetor Heat -- Cold.
- (3) Wing Flaps -- Retract to 20°.
- (4) Upon reaching an airspeed of approximately 65 MPH, retract flaps slowly.

## NORMAL LANDING.

- (1) Touchdown -- Main wheels first.
- (2) Landing Roll -- Lower nosewheel gently.
- (3) Braking -- Minimum required.

## AFTER LANDING.

- (1) Wing Flaps -- Up.
- (2) Carburetor Heat -- Cold.

## SECURE AIRCRAFT.

- (1) Mixture -- Idle cut-off (pulled full out).
- (2) All switches -- Off.
- (3) Brakes -- Set.
- (4) Control Lock -- Installed.

## MODIFIED FUEL MANAGEMENT PROCEDURES

With a combination of highly volatile fuel, high fuel temperature, high operating altitude, and low fuel flow rate in the tank outlet lines, there is a remote possibility of accumulating fuel vapor and encountering power irregularities on some airplanes. To minimize this possibility, the following operating procedures are recommended:

- (1) Take-off and climb to cruise altitude on "both" tanks.  
(This is consistent with current recommendations.)
- (2) When reaching cruise altitude above 5000 feet MSL, promptly switch the fuel selector valve from "both" tanks to either the "right" or "left" tank.
- (3) During cruise, use "left" and "right" tank as required.
- (4) Select "both" tanks for landing as currently recommended.

## POWER RECOVERY TECHNIQUES

In the remote event that vapor is present in sufficient amounts to cause a power irregularity, the following power recovery techniques should be followed:

### OPERATION ON A SINGLE TANK

Should power irregularities occur when operating on a single tank, power can be restored immediately by switching to the opposite tank. In addition, the vapor accumulation in the tank on which the power irregularity occurred will rapidly dissipate itself such that that tank will also be available for normal operation after it has been unused for approximately one (1) minute.

### OPERATION ON BOTH TANKS

Should power irregularities occur with the fuel selector on both tanks, the following steps are to be taken to restore power:

- (1) Switch to a single tank for a period of 60 seconds.
- (2) Then switch to the opposite tank and power will be restored.

## Section II

### DESCRIPTION AND OPERATING DETAILS

The following paragraphs describe the systems and equipment whose function and operation is not obvious when sitting in the airplane. This section also covers in somewhat greater detail some of the items listed in Check List form in Section I that require further explanation.

#### FUEL SYSTEM.

Fuel is supplied to the engine from two tanks, one in each wing. With the fuel selector valve on "BOTH," the total usable fuel for all flight conditions is 38 gallons for the standard tanks and 48 gallons for the optional long range tanks.

Fuel from each wing tank flows by gravity to a selector valve. Depending upon the setting of the selector valve, fuel from the left, right, or both tanks flows through a fuel strainer and carburetor to the engine induction system.

#### IMPORTANT

The fuel selector valve should be in the "BOTH" position for take-off, climb, landing, and maneuvers that involve prolonged slips or skids. Operation from either "LEFT" or "RIGHT" tank is reserved for cruising flight.

#### NOTE

When the fuel selector valve handle is in the "BOTH" position in cruising flight, unequal fuel flow from each tank may occur if the wings are not maintained exactly level. Resulting wing heaviness can be alleviated gradually by turning the selector valve handle to the tank in the "heavy" wing.

For fuel system servicing information, refer to Lubrication and Servicing Procedures in Section IV.




Figure 2-1.



## FUEL SYSTEM SCHEMATIC




Figure 2-2.

## ELECTRICAL SYSTEM.

Electrical energy is supplied by a 14-volt, direct-current system powered by an engine-driven alternator (see figure 2-3). A 12-volt battery is located on the left-hand forward portion of the firewall. Power is supplied to all electrical circuits through a split bus bar, one side containing electronic systems and the other side having general electrical systems. Both sides of the bus are on at all times except when either an external power source is connected or the ignition/starter switch is turned on; then a power contactor is automatically activated to open the circuit to the electronic bus. Isolating the electronic circuits in this manner prevents harmful transient voltages from damaging the transistors in the electronic equipment.

## AMMETER.

The ammeter indicates the flow of current, in amperes, from the alternator to the battery or from the battery to the aircraft electrical system. When the engine is operating and the master switch is "ON," the ammeter indicates the charging rate applied to the battery. In the event the alternator is not functioning or the electrical load exceeds the output of the alternator, the ammeter indicates the discharge rate of the battery.

## CIRCUIT BREAKERS AND FUSES.

The majority of electrical circuits in the airplane are protected by "push-to-reset" circuit breakers mounted on the instrument panel. Exceptions to this are the optional clock, flight hour recorder, and battery contactor closing (external power) circuits which have fuses mounted adjacent to the battery. Also, the cigar lighter is protected by a manually reset type circuit breaker mounted directly on the back of the lighter behind the instrument panel. The alternator field and wiring is protected by an automatically resetting circuit breaker.

## LANDING LIGHTS (OPT).

A three-position, push-pull switch controls the optional landing lights. To turn one lamp on for taxiing, pull the switch out to the first stop. To turn both lamps on for landing, pull the switch out to the second stop. To turn both lamps off, push the switch full in.




Figure 2-3.

### CONTROL WHEEL MAP LIGHT (OPT.)

A map light may be mounted on the bottom of the pilot's control wheel. The light illuminates the lower portion of the cabin just forward of the pilot and is helpful when checking maps and other flight data during night operations. To operate the light, first turn the "NAV LIGHTS" switch on, then adjust the map light's intensity with the knurled rheostat knob located at the bottom of the control wheel.

### FLASHING BEACON (OPT.)

The flashing beacon should not be used when flying through clouds or overcast; the flashing light reflected from water droplets or particles in the atmosphere, particularly at night, can produce vertigo and loss of orientation.

### CABIN HEATING, VENTILATING AND DEFROSTING SYSTEM.

For cabin ventilation, pull the "CABIN AIR" knob out. To raise the air temperature, pull the "CABIN HT" knob out approximately 1/4" to 1/2" for a small amount of cabin heat. Additional heat is available by pulling the knob out farther; maximum heat is available with the "CABIN HT" knob pulled full out and the "CABIN AIR" knob pushed full in. When no heat is desired in the cabin, the "CABIN HT" knob is pushed full in.

Front cabin heat and ventilating air is supplied by outlet holes spaced across a cabin manifold just forward of the pilot's and copilot's feet. Rear cabin heat and air is supplied by two ducts from the manifold, one extending down each side of the cabin to an outlet at the front door post at floor level. Windshield defrost air is also supplied by a duct leading from the cabin manifold.

Separate adjustable ventilators supply additional air; one near each upper corner of the windshield supplies air for the pilot and copilot, and two optional ventilators in the rear cabin ceiling supply air to the rear seat passengers.

### STARTING ENGINE.

During engine starting, open the throttle approximately 1/8 inch. In

warm temperatures, one or two strokes of the primer should be sufficient. In cold weather, up to six strokes of the primer may be necessary. If the engine is warm, no priming will be required. In extremely cold temperatures, it may be necessary to continue priming while cranking the engine.

Weak intermittent firing followed by puffs of black smoke from the exhaust stack indicates overpriming or flooding. Excess fuel can be cleared from the combustion chambers by the following procedure: Set the mixture control full lean and the throttle full open; then crank the engine through several revolutions with the starter. Repeat the starting procedure without any additional priming.

If the engine is underprimed (most likely in cold weather with a cold engine) it will not fire at all, and additional priming will be necessary. As soon as the cylinders begin to fire, open the throttle slightly to keep it running.

After starting, if the oil gage does not begin to show pressure within 30 seconds in the summertime and about twice that long in very cold weather, stop engine and investigate. Lack of oil pressure can cause serious engine damage. After starting, avoid the use of carburetor heat unless icing conditions prevail.

#### NOTE

Additional details for cold weather starting and operation may be found under "COLD WEATHER OPERATION" in this section.

## TAXIING.

When taxiing, it is important that speed and use of brakes be held to a minimum and that all controls be utilized (see Taxiing Diagram, figure 2-4) to maintain directional control and balance.

The carburetor heat control knob should be pushed full in during all ground operations unless heat is absolutely necessary. When the knob is pulled out to the heat position, air entering the engine is not filtered.

Taxiing over loose gravel or cinders should be done at low engine speed to avoid abrasion and stone damage to the propeller tips.




Figure 2-4.

## BEFORE TAKE-OFF.

### WARM-UP.

If the engine accelerates smoothly, the airplane is ready for take-off. Since the engine is closely cowled for efficient in-flight engine cooling, precautions should be taken to avoid overheating during prolonged engine operation on the ground. Also, long periods of idling may cause fouled spark plugs.

### MAGNETO CHECK.

The magneto check should be made at 1700 RPM as follows: Move ignition switch first to "R" position, and note RPM. Next move switch back to "BOTH" to clear the other set of plugs. Then move switch to the "L" position and note RPM. RPM drop should not exceed 125 RPM on either magneto or show greater than 50 RPM differential between magnetos. If there is a doubt concerning operation of the ignition system, RPM checks at higher engine speeds will usually confirm whether a deficiency exists.

An absence of RPM drop may be an indication of faulty grounding of one side of the ignition system or should be cause for suspicion that the magneto timing is set in advance of the setting specified.

## TAKE-OFF.

### POWER CHECK.

It is important to check full-throttle engine operation early in the take-off run. Any signs of rough engine operation or sluggish engine acceleration is good cause for discontinuing the take-off. If this occurs, you are justified in making a thorough full-throttle, static runup before another take-off is attempted. The engine should run smoothly and turn approximately 2260 to 2360 RPM with carburetor heat off.

#### NOTE

Carburetor heat should not be used during take-off unless it is absolutely necessary for obtaining smooth engine acceleration.

Full-throttle runups over loose gravel are especially harmful to propeller tips. When take-offs must be made over a gravel surface, it is very important that the throttle be advanced slowly. This allows the airplane to start rolling before high RPM is developed, and the gravel will be blown back of the propeller rather than pulled into it. When unavoidable small dents appear in the propeller blades, they should be immediately corrected as described in Section IV under propeller care.

Prior to take-off from fields above 5000 feet elevation, the mixture should be leaned to give maximum RPM in a full-throttle, static runup.

### WING FLAP SETTINGS.

Normal and obstacle clearance take-offs are performed with wing flaps up. The use of 10° flaps will shorten the ground run approximately 10%, but this advantage is lost in the climb to a 50-foot obstacle. Therefore, the use of 10° flaps is reserved for minimum ground runs or for take-off from soft or rough fields with no obstacles ahead.

If 10° flaps are used for a minimum ground run (with no obstacles), the flaps may be retracted as the airplane accelerates to the normal flaps-up climb speed of 80 to 90 MPH. When an obstacle is involved, use the best angle-of-climb speed of approximately 65 MPH with 10° of flaps. Also, it is preferable to leave the flaps extended rather than retract them in the climb to the obstacle. As soon as the obstacle is cleared, the flaps may be retracted as the airplane accelerates to the normal flaps-up climb speed. During a high altitude take-off in hot weather where climb would be marginal with 10° flaps, it is recommended that the flaps not be used for take-off.

Flap settings of 30° to 40° are not recommended at any time for take-off.

### PERFORMANCE CHARTS.

Consult the Take-Off Data chart in Section V for take-off distances under various gross weight, altitude, headwind, temperature, and runway surface conditions.

### CROSSWIND TAKE-OFFS.

Take-offs into strong crosswinds normally are performed with the minimum flap setting necessary for the field length to minimize the drift angle immediately after take-off. The airplane is accelerated to

a speed slightly higher than normal, then pulled off abruptly to prevent possible settling back to the runway while drifting. When clear of the ground, make a coordinated turn into the wind to correct for drift.

## CLIMB.

### CLIMB DATA.

For detailed data, refer to the Maximum Rate-Of-Climb Data chart in Section V.

### CLIMB SPEEDS.

Normal climbs are performed at 80 to 90 MPH with flaps up and full throttle for best engine cooling. The mixture should be full rich below 5000 feet and may be leaned above 5000 feet for smoother engine operation. The maximum rate-of-climb speeds range from 82 MPH at sea level to 79 MPH at 10,000 feet. If an obstacle dictates the use of a steep climb angle, the best angle-of-climb speed should be used with flaps up and full throttle. These speeds vary from 68 MPH at sea level to 74 MPH at 10,000 feet.

#### NOTE

Steep climbs at these low speeds should be of short duration to improve engine cooling.

## CRUISE.

Normal cruising is done between 65% and 75% power. The power settings required to obtain these powers at various altitudes and outside air temperatures can be determined by using your Cessna Power Computer or the OPERATIONAL DATA, Section V.

Cruising can be done more efficiently at high altitudes because of lower air density and therefore higher true airspeeds for the same power. This is illustrated in the following table which shows performance at 75% power at various altitudes.

All figures are based on lean mixture, 38 gallons of fuel (no reserve), zero wind, standard atmospheric conditions, and 2300 pounds gross weight.

## OPTIMUM CRUISE PERFORMANCE

ALTITUDE	RPM	TRUE AIRSPEED	RANGE
Sea Level	2490	123	575
5000 ft.	2600	128	600
9000 ft.	Full Throttle	132	620

To achieve the lean mixture fuel consumption figures shown in Section V, the mixture should be leaned as follows: pull mixture control out until engine RPM peaks and begins to fall off, then enrichen slightly back to peak RPM.

Carburetor ice, as evidenced by an unexplained drop in RPM, can be removed by application of full carburetor heat. Upon regaining the original RPM (with heat off), use the minimum amount of heat (by trial and error) to prevent ice from forming. Since the heated air causes a richer mixture, readjust the mixture setting when carburetor heat is to be used continuously in cruise flight.

The use of full carburetor heat is recommended during flight in heavy rain to avoid the possibility of engine stoppage due to excessive water ingestion or carburetor ice. The mixture setting should be readjusted for smoothest operation.

In extremely heavy rain, the use of partial carburetor heat (control approximately 2/3 out), and part throttle (closed at least one inch), may be necessary to retain adequate power. Power changes should be made cautiously followed by prompt adjustment of the mixture for smoothest operation.

## STALLS.

The stall characteristics are conventional and aural warning is provided by a stall warning horn which sounds between 5 and 10 MPH above the stall in all configurations.

Power-off stall speeds at maximum gross weight and aft c.g. position are presented on page 5-2 as calibrated airspeeds since indicated airspeeds are unreliable near the stall.

## LANDINGS.

Normal landings are made power-off with any flap setting desired. Slips should be avoided with flap settings greater than 30° due to a downward pitch encountered under certain combinations of airspeed, side slip angle, and center of gravity loadings.

### NOTE

Carburetor heat should be applied prior to any significant reduction or closing of the throttle.

### NORMAL LANDING.

Landings should be made on the main wheels first to reduce the landing speed and subsequent need for braking in the landing roll. The nose wheel is lowered to the runway gently after the speed has diminished to avoid unnecessary nose gear loads. This procedure is especially important in rough or soft field landings.

### SHORT FIELD LANDING.

For short field landings, make a power-off approach at approximately 69 MPH indicated airspeed with 40° of flaps. Touchdown should be made on the main wheels first. Immediately after touchdown, lower the nose gear to the ground and apply heavy braking as required. For maximum brake effectiveness after all three wheels are on the ground, retract the flaps, hold full nose up elevator and apply maximum possible brake pressure without sliding the tires.

### CROSSWIND LANDING.

When landing in a strong crosswind, use the minimum flap setting required for the field length. Although the crab or combination method of drift correction may be used, the wing-low method gives the best control. After touchdown, hold a straight course with the steerable nose wheel and occasional braking if necessary.

The maximum allowable crosswind velocity is dependent upon pilot capability rather than airplane limitations. With average pilot technique, direct crosswinds of 15 MPH can be handled with safety.

### BALKED LANDING (GO-AROUND).

In a balked landing (go-around) climb, reduce the wing flap setting

to 20° immediately after full power is applied. If obstacles must be cleared during the go-around climb, leave the wing flaps in the 10° to 20° range until the obstacles are cleared. After clearing any obstacles the flaps may be retracted as the airplane accelerates to the normal flaps-up climb speed of 80 to 90 MPH.

## COLD WEATHER OPERATION.

### STARTING.

Prior to starting on a cold morning, it is advisable to pull the propeller through several times by hand to "break loose" or "limber" the oil, thus conserving battery energy. In extremely cold (0°F and lower) weather, the use of an external pre-heater and an external power source are recommended whenever possible to obtain positive starting and to reduce wear and abuse to the engine and electrical system. Pre-heat will thaw the oil trapped in the oil cooler, which probably will be congealed prior to starting in extremely cold temperatures. When using an external power source, the position of the master switch is important. Refer to Section VI under GROUND SERVICE PLUG RECEPTACLE for operating details.

Cold weather starting procedures are as follows:

#### With Preheat:

- (1) With ignition switch "OFF" and throttle closed, prime the engine four to eight strokes as the propeller is being turned over by hand.

### NOTE

Use heavy strokes of primer for best atomization of fuel. After priming, push primer all the way in and turn to locked position to avoid possibility of engine drawing fuel through the primer.

- (2) Propeller Area -- Clear.
- (3) Master Switch -- "ON."
- (4) Throttle -- Open 1/8".
- (5) Ignition Switch -- "START."
- (6) Release ignition switch to "BOTH" when engine starts.
- (7) Oil Pressure -- Check.

### Without Preheat:

- (1) Prime the engine six to ten strokes while the propeller is being turned by hand with throttle closed. Leave primer charged and ready for stroke.
- (2) Propeller Area -- Clear.
- (3) Master Switch -- "ON."
- (4) Pump throttle rapidly to full open twice. Return to 1/8" open position.
- (5) Ignition Switch -- "START."
- (6) Release ignition switch to "BOTH" when engine starts.
- (7) Continue to prime engine until it is running smoothly, or alternately pump throttle rapidly over first 1/4 to total travel.
- (8) Oil Pressure -- Check.
- (9) Pull carburetor heat knob full on after engine has started. Leave on until engine is running smoothly.
- (10) Lock Primer.

### NOTE

If the engine does not start during the first few attempts, or if engine firing diminishes in strength, it is probable that the spark plugs have been frosted over. Preheat must be used before another start is attempted.

### IMPORTANT

Pumping the throttle may cause raw fuel to accumulate in the intake air duct, creating a fire hazard in the event of a backfire. If this occurs, maintain a cranking action to suck flames into the engine. An outside attendant with a fire extinguisher is advised for cold starts without preheat.

During cold weather operations, no indication will be apparent on the oil temperature gage prior to take-off if outside air temperatures are very cold. After a suitable warm-up period (2 to 5 minutes at 1000 RPM), accelerate the engine several times to higher engine RPM. If the engine accelerates smoothly and the oil pressure remains normal and steady, the airplane is ready for take-off.

### FLIGHT OPERATIONS.

Take-off is made normally with carburetor heat off. Avoid excessive leaning in cruise.

Carburetor heat may be used to overcome any occasional engine roughness due to ice.

When operating in sub-zero temperature, avoid using partial carburetor heat. Partial heat may increase the carburetor air temperature to the 32° to 70°F range, where icing is critical under certain atmospheric conditions.

Refer to Section VI for cold weather equipment.

### HOT WEATHER OPERATION.

Refer to the general warm temperature starting information under STARTING ENGINE in this section. Avoid prolonged engine operation on the ground.

# Section III

## OPERATING LIMITATIONS

### OPERATIONS AUTHORIZED.

Your Cessna exceeds the requirements of airworthiness as set forth by the United States Government, and is certificated under FAA Type Certificate No. 3A12 as Cessna Model No. 172K.

With standard equipment, the airplane is approved for day and night operations under VFR. Additional optional equipment is available to increase its utility and to make it authorized for use under IFR day and night. An owner of a properly equipped Cessna is eligible to obtain approval for its operation on single-engine scheduled airline service under VFR. Your Cessna Dealer will be happy to assist you in selecting equipment best suited to your needs.

### MANEUVERS - NORMAL CATEGORY.

This airplane is certificated in both the normal and utility category. The normal category is applicable to airplanes intended for non-aerobatic operations. These include any maneuvers incidental to normal flying, stalls (except whip stalls) and turns in which the angle of bank is not more than 60°. In connection with the foregoing, the following gross weight and flight load factors apply:

Gross Weight . . . . .	2300 lbs
Flight Load Factor	
*Flaps Up . . . . .	+3.8      -1.52
*Flaps Down . . . . .	+3.5

\*The design load factors are 150% of the above, and in all cases, the structure meets or exceeds design loads.

Your airplane must be operated in accordance with all FAA-approved markings, placards and check lists in the airplane. If there is any information in this section which contradicts the FAA-approved markings, placards and check lists, it is to be disregarded.



## MANEUVERS - UTILITY CATEGORY.

This airplane is not designed for purely aerobatic flight. However, in the acquisition of various certificates such as commercial pilot, instrument pilot and flight instructor, certain maneuvers are required by the FAA. All of these maneuvers are permitted in this airplane when operated in the utility category. In connection with the utility category, the following gross weight and flight load factors apply, with maximum entry speeds for maneuvers as shown:

Gross Weight . . . . .	2000 lbs
Flight Maneuvering Load Factor	
Flaps Up . . . . .	+4.4      -1.76
Flaps Down . . . . .	+3.5

In the utility category, the baggage compartment and rear seat must not be occupied. No aerobatic maneuvers are approved except those listed below:

<u>MANEUVER</u>	<u>MAXIMUM ENTRY SPEED</u>
Chandelles . . . . .	122 mph (106 knots)
Lazy Eights . . . . .	122 mph (106 knots)
Steep Turns . . . . .	122 mph (106 knots)
Spins . . . . .	Slow Deceleration
Stalls (Except Whip Stalls) . . . . .	Slow Deceleration

Aerobatics that may impose high inverted loads should not be attempted. The important thing to bear in mind in flight maneuvers is that the airplane is clean in aerodynamic design and will build up speed quickly with the nose down. Proper speed control is an essential requirement for execution of any maneuver, and care should always be exercised to avoid excessive speed which in turn can impose excessive loads. In the execution of all maneuvers, avoid abrupt use of controls.

## AIRSPED LIMITATIONS (CAS).

The following is a list of the certificated calibrated airspeed (CAS) limitations for the airplane.

Never Exceed Speed (glide or dive, smooth air) . . . . .	174 MPH
Maximum Structural Cruising Speed . . . . .	140 MPH

Maximum Speed, Flaps Extended . . . . .	100 MPH
*Maximum Maneuvering Speed . . . . .	122 MPH

\*The maximum speed at which abrupt control travel can be used without exceeding the design load factor.

## AIRSPED INDICATOR MARKINGS.

The following is a list of the certificated calibrated airspeed markings (CAS) for the airplane.

Never Exceed (glide or dive, smooth air) . . . . .	174 MPH (red line)
Caution Range . . . . .	140-174 MPH (yellow arc)
Normal Operating Range. . . . .	59-140 MPH (green arc)
Flap Operating Range . . . . .	52-100 MPH (white arc)

## ENGINE OPERATION LIMITATIONS.

Power and Speed . . . . .	150 BHP at 2700 RPM
---------------------------	---------------------

## ENGINE INSTRUMENT MARKINGS.

### OIL TEMPERATURE GAGE.

Normal Operating Range. . . . .	Green Arc
Maximum Allowable . . . . .	245°F (red line)

### OIL PRESSURE GAGE.

Minimum Idling. . . . .	25 psi (red line)
Normal Operating Range. . . . .	60-90 psi (green arc)
Maximum . . . . .	100 psi (red line)

### FUEL QUANTITY INDICATORS.

Empty (2.0 gallons unusable each tank) . . . . .	E (red line)
--	--------------

### TACHOMETER.

Normal Operating Range:	
At sea level . . . . .	2200-2500 (inner green arc)
At 5000 feet . . . . .	2200-2600 (middle green arc)
At 10,000 feet . . . . .	2200-2700 (outer green arc)
Maximum Allowable. . . . .	2700 (red line)

**CARBURETOR AIR TEMPERATURE GAGE (OPT).**

Icing Range . . . . . -15° to 5°C (yellow arc)

**WEIGHT AND BALANCE.**

The following information will enable you to operate your Cessna with- in the prescribed weight and center of gravity limitations. To figure the weight and balance for your particular airplane, use the Sample Problem, Loading Graph, and Center of Gravity Moment Envelope as follows:

Take the licensed Empty Weight and Moment/1000 from the Weight and Balance Data sheet, plus any change noted on forms FAA-337, carried in your airplane, and write them down in the proper columns. Using the Loading Graph, determine the moment/1000 of each item to be carried. Total the weights and moments/1000 and use the Center of Gravity Moment Envelope to determine whether the point falls within the envelope, and if the loading is acceptable.

**NOTE**

The Weight and Balance Data Sheet noted above is included in the aircraft file. The Loading Graph and Center of Gravity Moment Envelope shown in this section are also on the sheet titled Loading/Center of Gravity Charts and Weighing Pro- cedures which is provided in the aircraft file.

SAMPLE LOADING PROBLEM	SAMPLE AIRPLANE		YOUR AIRPLANE	
	Weight (lbs.)	Moment (lb. -ins. /1000)	Weight (lbs.)	Moment (lb. -ins. /1000)
1. Licensed Empty Weight (Sample Airplane) . . .	1306	47.6		
2. Oil (8 qts. - Full oil may be assumed for all flights). . . . .	15	-0.2	15	-0.2
3. Fuel (Standard - 38 Gal at 6#/Gal). . . . .	228	10.9		
Fuel (Long Range - 48 Gal at 6#/Gal). . . . .				
4. Pilot and Front Passenger . . . . .	340	12.2		
5. Rear Passengers . . . . .	340	23.8		
6. Baggage (or Passenger on Auxiliary Seat) . . .	71	6.7		
7. TOTAL WEIGHT AND MOMENT	2300	101.0		

8. Locate this point (2300 at 101.0) on the center of gravity moment envelope, and since this point falls within the envelope, the loading is acceptable.

**PART 'C' - LOADING INFORMATION (DISPOSABLE LOAD)**

The total moment change when the landing gear is retracted in Lbs. inches is N/A.

The appropriate lever arms are: -

ITEM	WEIGHT (Lbs.)	LEVER ARM (in)	MOMENT (Lbs./in)
Fuel in main tanks	228	48	10944
Fuel in aux. tanks		N/A	
Engine oil	Included in Basic Weight		
Forward Baggage Area 1		N/A	
Forward Baggage Area 2		N/A	
Rear Baggage Area 1	120 lbs	94.3	
	max		
Rear Baggage Area 2		N/A	
Pilot Rear Seat		35.9	
Passengers Row 2 seats		70	
Passengers Row 3 seats		N/A	
Passengers Row 4 seats		N/A	
Passengers Row 5 seats		N/A	

Fuel density 7.2 Lb./Gall. And oil density 9.0 Lb./Gall

Note: To obtain the total loaded weight of the aircraft, add to the basic weight the weights of the variable and disposable load items to be carried for the particular role.

This schedule was prepared on the 26 May 2004 and supersedes all previous issues

Signed: \_\_\_\_\_

Position: Chief Engineer.

For and on behalf of Tayflite Engineering Ltd  
Perth Airport Perth PH2 6NP

Note: The commander of an aircraft registered in the United Kingdom shall satisfy himself before the aircraft takes off that the load carried by the aircraft is of such a weight and is so distributed and secured that it may be safely carried on the intended flight (ANO 2000 Article 35)

LOAD WEIGHT (POUNDS)

LOAD MOMENT / 1000 (POUND - INCHES)

R AIR TEMPERATURE GAGE (OPT).  
 ge . . . . . -15° to 5°C (yellow arc)

**AND BALANCE.**

wing information will enable you to operate your Cessna with-  
 bed weight and center of gravity limitations. To figure the  
 ance for your particular airplane, use the Sample Problem,  
 1, and Center of Gravity Moment Envelope as follows:


icensed Empty Weight and Moment/1000 from the Weight  
 ata sheet, plus any change noted on forms FAA-337,  
 r airplane, and write them down in the proper columns.  
 ding Graph, determine the moment/1000 of each item to  
 total the weights and moments/1000 and use the Center of  
 nt Envelope to determine whether the point falls within the  
 if the loading is acceptable.


**NOTE**

Weight and Balance Data Sheet noted above is included  
 aircraft file. The Loading Graph and Center of Gravity  
 ent Envelope shown in this section are also on the sheet  
 Loading/Center of Gravity Charts and Weighing Pro-  
 ces which is provided in the aircraft file.

LOADING PROBLEM	SAMPLE AIRPLANE		YOUR AIRPLANE	
	Weight (lbs.)	Moment (lb.-ins./1000)	Weight (lbs.)	Moment (lb.-ins./1000)
Weight (Sample Airplane) . . . . .	1306	47.6		
Oil may be assumed . . . . .	15	-0.2	15	-0.2
38 Gal at 6#/Gal). . . . .	228	10.9		
48 Gal at 6#/Gal). . . . .				
Passenger . . . . .	340	12.2		
Passenger . . . . .	340	23.8		
Passenger on Auxiliary Seat) . . . . .	71	6.7		
<b>TOTAL WEIGHT AND MOMENT</b>	<b>2300</b>	<b>101.0</b>		

(2300 at 101.0) on the center of gravity moment envelope,  
 point falls within the envelope, the loading is acceptable.





## Section IV

### CARE OF THE AIRPLANE



If your airplane is to retain that new plane performance and dependability, certain inspection and maintenance requirements must be followed. It is wise to follow a planned schedule of lubrication and preventative maintenance based on climatic and flying conditions encountered in your locality.

Keep in touch with your Cessna Dealer and take advantage of his knowledge and experience. He knows your airplane and how to maintain it. He will remind you when lubrications and oil changes are necessary, and about other seasonal and periodic services.

### GROUND HANDLING.

The airplane is most easily and safely maneuvered by hand with the tow-bar attached to the nosewheel.

#### NOTE

When using the tow-bar, never exceed the turning angle of 30°, either side of center, or damage to the gear will result.

### MOORING YOUR AIRPLANE.

Proper tie-down procedure is your best precaution against damage to your parked airplane by gusty or strong winds. To tie down your airplane securely, proceed as follows:

- (1) Set the parking brake and install the control wheel lock.
- (2) Tie sufficiently strong ropes or chains (700 pounds tensile strength) to wing, tail and nose tie-down rings and secure each rope to a ramp tie-down.

- (3) Install a surface control lock over the fin and rudder.
- (4) Install a pitot tube cover.

## WINDSHIELD - WINDOWS.

The plastic windshield and windows should be cleaned with an aircraft windshield cleaner. Apply the cleaner sparingly with soft cloths, and rub with moderate pressure until all dirt, oil scum and bug stains are removed. Allow the cleaner to dry, then wipe it off with soft flannel cloths.

If a windshield cleaner is not available, the plastic can be cleaned with soft cloths moistened with Stoddard solvent to remove oil and grease.

### NOTE

Never use gasoline, benzine, alcohol, acetone, carbon tetrachloride, fire extinguisher or anti-ice fluid, lacquer thinner or glass cleaner to clean the plastic. These materials will attack the plastic and may cause it to craze.

Follow by carefully washing with a mild detergent and plenty of water. Rinse thoroughly, then dry with a clean moist chamois. Do not rub the plastic with a dry cloth since this builds up an electrostatic charge which attracts dust. Waxing with a good commercial wax will finish the cleaning job. A thin, even coat of wax, polished out by hand with clean soft flannel cloths, will fill in minor scratches and help prevent further scratching.

Do not use a canvas cover on the windshield unless freezing rain or sleet is anticipated since the cover may scratch the plastic surface.

## PAINTED SURFACES.

The painted exterior surfaces of your new Cessna have a durable, long lasting finish and, under normal conditions, require no polishing or buffing. Approximately 15 days are required for the paint to cure completely; in most cases, the curing period will have been completed prior to delivery of the airplane. In the event that polishing or buffing is required within the curing period, it is recommended that the work be done by someone experienced in handling uncured paint. Any Cessna Dealer can accomplish this work.

Generally, the painted surfaces can be kept bright by washing with water and mild soap, followed by a rinse with water and drying with cloths or a chamois. Harsh or abrasive soaps or detergents which cause corrosion or make scratches should never be used. Remove stubborn oil and grease with a cloth moistened with Stoddard solvent.

Waxing is unnecessary to keep the painted surfaces bright. However, if desired, the airplane may be waxed with a good automotive wax. A heavier coating of wax on the leading edges of the wings and tail and on the engine nose cap and propeller spinner will help reduce the abrasion encountered in these areas.

When the airplane is parked outside in cold climates and it is necessary to remove ice before flight, care should be taken to protect the painted surfaces during ice removal with chemical liquids. A 50-50 solution of isopropyl alcohol and water will satisfactorily remove ice accumulations without damaging the paint. A solution with more than 50% alcohol is harmful and should be avoided. While applying the de-icing solution, keep it away from the windshield and cabin side windows since the alcohol will attack the plastic and may cause it to craze.

## ALUMINUM SURFACES.

The clad aluminum surfaces of your Cessna may be washed with clear water to remove dirt; oil and grease may be removed with gasoline, naphtha, carbon tetrachloride or other non-alkaline solvents. Dulled aluminum surfaces may be cleaned effectively with an aircraft aluminum polish.

After cleaning, and periodically thereafter, waxing with a good automotive wax will preserve the bright appearance and retard corrosion. Regular waxing is especially recommended for airplanes operated in salt water areas as a protection against corrosion.

## PROPELLER CARE.

Preflight inspection of propeller blades for nicks, and wiping them occasionally with an oily cloth to clean off grass and bug stains will assure long, trouble-free service. It is vital that small nicks on the propeller, particularly near the tips and on the leading edges, are dressed out as soon as possible since these nicks produce stress concentrations,



and if ignored, may result in cracks. Never use an alkaline cleaner on the blades; remove grease and dirt with carbon tetrachloride or Stoddard solvent.

## INTERIOR CARE.

To remove dust and loose dirt from the upholstery and carpet, clean the interior regularly with a vacuum cleaner.

Blot up any spilled liquid promptly, with cleansing tissue or rags. Don't pat the spot; press the blotting material firmly and hold it for several seconds. Continue blotting until no more liquid is taken up. Scrape off sticky materials with a dull knife, then spot-clean the area.

Oily spots may be cleaned with household spot removers, used sparingly. Before using any solvent, read the instructions on the container and test it on an obscure place on the fabric to be cleaned. Never saturate the fabric with a volatile solvent; it may damage the padding and backing materials.

Soiled upholstery and carpet may be cleaned with foam-type detergent, used according to the manufacturer's instructions. To minimize wetting the fabric, keep the foam as dry as possible and remove it with a vacuum cleaner.

The plastic trim, headliner, instrument panel and control knobs need only be wiped off with a damp cloth. Oil and grease on the control wheel and control knobs can be removed with a cloth moistened with Stoddard solvent. Volatile solvents, such as mentioned in paragraphs on care of the windshield, must never be used since they soften and craze the plastic.

## INSPECTION SERVICE AND INSPECTION PERIODS.

With your airplane you will receive an Owner's Service Policy. Coupons attached to the policy entitle you to an initial inspection and the first 100-hour inspection at no charge. If you take delivery from your Dealer, he will perform the initial inspection before delivery of the airplane to you. If you pick up the airplane at the factory, plan to take it to your Dealer reasonably soon after you take delivery on it. This will permit him to check it over and to make any minor adjustments that may appear

necessary. Also, plan an inspection by your Dealer at 100 hours or 180 days, whichever comes first. This inspection also is performed by your Dealer for you at no charge. While these important inspections will be performed for you by any Cessna Dealer, in most cases you will prefer to have the Dealer from whom you purchased the airplane accomplish this work.

Federal Aviation Regulations require that all airplanes have a periodic (annual) inspection as prescribed by the administrator, and performed by a person designated by the administrator. In addition, 100-hour periodic inspections made by an "appropriately-rated mechanic" are required if the airplane is flown for hire. The Cessna Aircraft Company recommends the 100-hour periodic inspection for your airplane. The procedure for this 100-hour inspection has been carefully worked out by the factory and is followed by the Cessna Dealer Organization. The complete familiarity of the Cessna Dealer Organization with Cessna equipment and with factory-approved procedures provides the highest type of service possible at lower cost.



## AIRCRAFT FILE.

There are miscellaneous data, information and licenses that are a part of the aircraft file. The following is a check list for that file. In addition, a periodic check should be made of the latest Federal Aviation Regulations to insure that all data requirements are met.

A. To be displayed in the aircraft at all times:

- (1) Aircraft Airworthiness Certificate (Form FAA-1362B).
- (2) Aircraft Registration Certificate (Form FAA-500A).
- (3) Aircraft Radio Station License (Form FCC-404, if transmitter installed).

B. To be carried in the aircraft at all times:

- (1) Weight and Balance, and associated papers (latest copy of the Repair and Alteration Form, Form FAA-337, if applicable).
- (2) Aircraft Equipment List.

C. To be made available upon request:

- (1) Aircraft Log Book.
- (2) Engine Log Book.

### NOTE

Cessna recommends that these items, plus the Owner's Manual, "Cessna Flight Guide" (Flight Computer), and Service Policies, be carried in the aircraft at all times.

Most of the items listed are required by the United States Federal Aviation Regulations. Since the regulations of other nations may require other documents and data, owners of exported aircraft should check with their own aviation officials to determine their individual requirements.

## LUBRICATION AND SERVICING PROCEDURES

Specific servicing information is provided here for items requiring daily attention. A Servicing Intervals Check List is included to inform the pilot when to have other items checked and serviced.

### DAILY

#### FUEL TANK FILLERS:

Service after each flight with 80/87 minimum grade fuel. The capacity of each tank is 21 gallons. When optional long range tanks are installed, the capacity of each tank is 26 gallons.

#### FUEL STRAINER:

Before the first flight of the day and after each refueling, pull out fuel strainer drain knob for about four seconds, to clear fuel strainer of possible water and sediment. Release drain knob, then check that strainer drain is closed after draining. If water is observed, there is a possibility that the fuel tank sumps contain water. Thus, the fuel tank sump drain plugs and fuel line drain plug should be removed to check for the presence of water.

#### OIL DIPSTICK:

Check oil level before each flight. Do not operate on less than 6 quarts. To minimize loss of oil through breather, fill to 7 quart level for normal flights of less than 3 hours. For extended flight, fill to 8 quarts. If optional oil filter is installed, one additional quart is required when the filter element is changed.

#### OIL FILLER:

When preflight check shows low oil level, service with aviation grade engine oil; SAE 50 above 60°F, SAE 10W30 or SAE 30 at temperatures from 0° to 70°F, and SAE 10W30 or SAE 20 at temperatures below 10°F. (Multi-viscosity oil with a range of SAE 10W30 is recommended for improved starting and lubrication during warm-up in cold weather.) Detergent or dispersant oil, conforming to Lycoming Specification No. 301E, must be used. Your Cessna Dealer can supply approved brands of oil.

### NOTE

To promote faster ring seating and improved oil control, your Cessna was delivered from the factory with straight mineral oil (non-detergent). This "break-in" oil should be used only for the first 50 hours of operation, or until oil consumption has stabilized at which time it must be replaced with detergent oil.



## SERVICING INTERVALS CHECK LIST

### FIRST 25 HOURS

ENGINE OIL SUMP, OIL COOLER AND OIL FILTER -- After first 25 hours of operation, drain engine oil sump and oil cooler and clean both the oil suction strainer and oil pressure screen. If an optional oil filter is installed, change filter element at this time. Refill sump with straight mineral oil (non-detergent) and use until a total of 50 hours have accumulated or oil consumption has stabilized, then change to detergent oil.

### EACH 50 HOURS

BATTERY -- Check and service. Check oftener (at least every 30 days) if operating in hot weather.  
ENGINE OIL SUMP, OIL COOLER AND OIL FILTER -- On airplanes not equipped with an optional oil filter, drain the engine oil sump and oil cooler and clean both the oil suction strainer and oil pressure screen. On the airplanes which have an optional oil filter, the oil change interval may be extended to 100-hour intervals providing the oil filter element is changed at 50-hour intervals. Change engine oil at least every four months even though less than 50 hours have accumulated. Reduce intervals for prolonged operation in dusty areas, cold climates, or when short flights and long idle periods result in sludging conditions.  
CARBURETOR AIR FILTER -- Clean or replace. Under extremely dusty conditions, daily maintenance of the filter is recommended.  
NOSE GEAR TORQUE LINKS -- Lubricate. When operating under dusty conditions, more frequent lubrication is recommended.

### EACH 100 HOURS

SPARK PLUGS -- Clean, test and regap.  
BRAKE MASTER CYLINDERS -- Check and fill.  
SHIMMY DAMPENER -- Check and fill.  
FUEL STRAINER -- Disassemble and clean.  
FUEL TANK SUMP DRAINS -- Drain water and sediment.  
FUEL LINE DRAIN PLUG -- Drain water and sediment.  
VACUUM SYSTEM OIL SEPARATOR (OPT) -- Clean.  
SUCTION RELIEF VALVE INLET SCREEN (OPT) -- Clean.

## SERVICING INTERVALS CHECK LIST

(Continued)

### EACH 500 HOURS

VACUUM SYSTEM AIR FILTER (OPT) -- Replace filter element. Replace sooner if suction gage reading drops to 4.6 in. Hg.  
WHEEL BEARINGS -- Lubricate at first 100 hours and at 500 hours thereafter. Reduce lubrication interval to 100 hours when operating in dusty or seacoast areas, during periods of extensive taxiing, or when numerous take-offs and landings are made.

### AS REQUIRED

NOSE GEAR SHOCK STRUT -- Keep filled with fluid and inflated to 45 psi.





## OWNER FOLLOW-UP SYSTEM

Your Cessna Dealer has an owner follow-up system to notify you when he receives information that applies to your Cessna. In addition, if you wish, you may choose to receive similar notification directly from the Cessna Service Department. A subscription card is supplied in your aircraft file for your use, should you choose to request this service. Your Cessna Dealer will be glad to supply you with details concerning these follow-up programs, and stands ready through his Service Department to supply you with fast, efficient, low cost service.

## PUBLICATIONS

Various publications and flight operation aids are furnished in the aircraft when delivered from the factory. These items are listed below.

- OWNER'S MANUALS FOR YOUR AIRCRAFT ELECTRONICS AND AUTOPILOT
- CESSNA FLIGHT GUIDE (FLIGHT COMPUTER)
- SALES AND SERVICE DEALER DIRECTORY

The following additional publications, plus many other supplies that are applicable to your aircraft, are available from your Cessna Dealer.

- SERVICE MANUALS AND PARTS CATALOGS FOR YOUR AIRCRAFT ENGINE AND ACCESSORIES ELECTRONICS AND AUTOPILOT

Your Cessna Dealer has a current catalog of all available Customer Services Supplies, many of which he keeps on hand. If supplies are not in stock, your Cessna Dealer will be happy to order for you.

## Section V

## OPERATIONAL DATA

The operational data shown on the following pages are compiled from actual tests with the airplane and engine in good condition and using average piloting technique and best power mixture. You will find this data a valuable aid when planning your flights.

A power setting selected from the range chart usually will be more efficient than a random setting, since it will permit you to estimate your fuel consumption more accurately. You will find that using the charts and your Power Computer will pay dividends in overall efficiency.

Cruise and range performance shown in this section is based on flight tests using a McCauley 1C172/MTM 7653 propeller. Other conditions of the tests are shown in the chart headings. Allowances for fuel reserve, headwinds, take-offs, and climb, and variations in mixture leaning technique should be made and are in addition to those shown on the chart. Other indeterminate variables such as carburetor metering-characteristics, engine and propeller conditions, and turbulence of the atmosphere may account for variations of 10% or more in maximum range.

Remember that the charts contained herein are based on standard day conditions. For more precise power, fuel consumption, and endurance information, consult the Cessna Flight Guide (Power Computer) supplied with your aircraft. With the Flight Guide, you can easily take into account temperature variations from standard at any flight altitude.

## AIRSPEED CORRECTION TABLE

	IAS	40	50	60	70	80	90	100	110	120	130	140
FLAPS UP	CAS	55	58	65	72	82	91	101	110	120	129	139
FLAPS DOWN	CAS	48	54	63	72	82	93	105	•	•	•	•

Figure 5-1.

## POWER OFF STALLING SPEEDS MPH - CAS

	CONDITION	ANGLE OF BANK			
		0°	20°	40°	60°
2300 LBS. GROSS WEIGHT	FLAPS UP	57	59	65	81
	FLAPS 10°	52	54	59	74
	FLAPS 40°	49	51	56	69

Figure 5-2.

## TAKE-OFF DATA

### TAKE-OFF DISTANCE FROM HARD SURFACE RUNWAY WITH FLAPS UP

GROSS WEIGHT POUNDS	IAS AT 30' MPH	HEAD WIND KNOTS	AT SEA LEVEL & 59°		AT 2500 FT. & 50° F		AT 5000 FT. & 41° F		AT 7500 FT. & 32° F		TOTAL TO CLEAR 50 FT OBS
			GROUND RUN	TOTAL TO CLEAR 50 FT OBS	GROUND RUN	TOTAL TO CLEAR 50 FT OBS	GROUND RUN	TOTAL TO CLEAR 50 FT OBS	GROUND RUN	TOTAL TO CLEAR 50 FT OBS	
2300	68	0	865	1525	1040	1910	1255	2480	1565	3655	3655
		20	615	1170	750	1485	920	1955	1160	3110	
2000	63	0	630	1095	755	1325	905	1625	1120	2155	2155
		20	435	820	530	1065	645	1250	810	1685	
1700	58	0	435	780	520	920	625	1085	765	1370	1370
		20	290	570	355	680	430	820	535	1040	
		20	175	385	215	470	270	575	345	745	745

NOTES: 1. Increase distance 10% for each 25° F above standard temperature for particular altitude.  
 2. For operation on a dry, grass runway, increase distances (both "ground run" and "total to clear 50 ft. obstacle") by 7% of the "total to clear 50 ft. obstacle" figure.

## MAXIMUM RATE-OF-CLIMB DATA

GROSS WEIGHT POUNDS	AT SEA LEVEL & 59° F		AT 5000 FT. & 41° F		AT 10,000 FT. & 29° F		AT 15,000 FT. & 5° F	
	IAS MPH	RATE OF CLIMB FT/MIN	IAS MPH	RATE OF CLIMB FT/MIN	IAS MPH	RATE OF CLIMB FT/MIN	IAS MPH	RATE OF CLIMB FT/MIN
2300	82	645	81	435	79	230	78	22
2000	79	840	79	610	76	380	75	155
1700	77	1085	76	825	73	570	72	315

NOTES: 1. Flaps up, full throttle, mixture leaned for smooth operation above 5000 ft.  
 2. Fuel used includes warm up and take-off allowance.  
 3. For hot weather, decrease rate of climb 20 ft./min. for each 10° F above standard day temperature for particular altitude.

Figure 5-3.



# CRUISE & RANGE PERFORMANCE

## SKYHAWK

Gross Weight- 2300 Lbs.  
Standard Conditions  
Zero Wind Lean Mixture

NOTE: Maximum cruise is normally limited to 75% power. Cruise speed for the standard Model 172 is approximately one MPH less than shown below for the Skyhawk configuration.

ALT.	RPM	% BHP	TAS MPH	GAL / HOUR	38 GAL (NO RESERVE)		48 GAL (NO RESERVE)	
					ENDR. HOURS	RANGE MILES	ENDR. HOURS	RANGE MILES
2500	2700	86	134	9.7	3.9	525	4.9	660
	2600	79	129	8.6	4.4	570	5.6	720
	2500	72	123	7.8	4.9	600	6.2	760
	2400	65	117	7.2	5.3	620	6.7	780
	2300	58	111	6.7	5.7	630	7.2	795
	2200	52	103	6.3	6.1	625	7.7	790
5000	2700	82	134	9.0	4.2	565	5.3	710
	2600	75	128	8.1	4.7	600	5.9	760
	2500	68	122	7.4	5.1	625	6.4	790
	2400	61	116	6.9	5.5	635	6.9	805
	2300	55	108	6.5	5.9	635	7.4	805
	2200	49	100	6.0	6.3	630	7.9	795
7500	2700	78	133	8.4	4.5	600	5.7	755
	2600	71	127	7.7	4.9	625	6.2	790
	2500	64	121	7.1	5.3	645	6.7	810
	2400	58	113	6.7	5.7	645	7.2	820
	2300	52	105	6.2	6.1	640	7.7	810
10,000	2650	70	129	7.6	5.0	640	6.3	810
	2600	67	125	7.3	5.2	650	6.5	820
	2500	61	118	6.9	5.5	655	7.0	830
	2400	55	110	6.4	5.9	650	7.5	825
	2300	49	100	6.0	6.3	635	8.0	800
12,500	2600	63	123	7.0	5.4	665	6.8	840
	2500	57	115	6.6	5.8	665	7.3	835
	2400	51	105	6.2	6.1	645	7.8	815

Figure 5-4.

# LANDING DATA

## LANDING DISTANCE ON HARD SURFACE RUNWAY NO WIND - 40° FLAPS - POWER OFF

GROSS WEIGHT LBS.	APPROACH IAS MPH	@ S.L. & 59° F		@ 2500 ft. & 50° F		@ 5000 ft. & 41° F		@ 7500 ft. & 32° F	
		GROUND ROLL	TOTAL TO CLEAR 50' OBS.	GROUND ROLL	TOTAL TO CLEAR 50' OBS.	GROUND ROLL	TOTAL TO CLEAR 50' OBS.	GROUND ROLL	TOTAL TO CLEAR 50' OBS.
2300	69	520	1250	560	1310	605	1385	650	1455

NOTES: 1. Reduce landing distance 10% for each 5 knot headwind.  
2. For operation on a dry, grass runway, increase distances (both "ground roll" and "total to clear 50 ft. obstacle") by 20% of the "total to clear 50 ft. obstacle" figure.

Figure 5-5.



## MAXIMUM GLIDE

- SPEED 80 MPH (IAS)
- PROPELLER WINDMILLING
- FLAPS UP ● ZERO WIND




Figure 5-6.

## Section VI

### OPTIONAL SYSTEMS

This section contains a description, operating procedures, and performance data (when applicable) for some of the optional equipment which may be installed in your Cessna. Owner's Manual Supplements are provided to cover operation of other optional equipment systems when installed in your airplane. Contact your Cessna Dealer for a complete list of available optional equipment.

#### LONG RANGE FUEL TANKS

Special wings with long range fuel tanks are available to replace the standard wings and fuel tanks for greater endurance and range. When these tanks are installed, the total usable fuel for all flight conditions is 48 gallons.

#### COLD WEATHER EQUIPMENT

##### WINTERIZATION KIT.

For continuous operation in temperatures consistently below 20°F, the Cessna winterization kit, available from your Cessna Dealer, should be installed to improve engine operation. The kit consists of a large baffle which attaches to the lower cowling, a baffle partially covering the oil cooler, and insulation for the crankcase breather line. Once installed, the crankcase breather insulation is approved for permanent use in both cold and hot weather.

## GROUND SERVICE PLUG RECEPTACLE.

A ground service plug receptacle may be installed to permit use of an external power source for cold weather starting and during lengthy maintenance work on the airplane electrical system (with the exception of electronic equipment).

### NOTE

Electrical power for the airplane electrical circuits is provided through a split bus bar having all electronic circuits on one side of the bus and other electrical circuits on the other side of the bus. When an external power source is connected, a contactor automatically opens the circuit to the electronic portion of the split bus bar as a protection against damage to the semi-conductors in the electronic equipment by transient voltages from the power source. Therefore, the external power source can not be used as a source of power when checking electronic components.

Just before connecting an external power source (generator type or battery cart), the master switch should be turned "ON."

The ground service plug receptacle circuit incorporates a polarity reversal protection. Power from the external power source will flow only if the ground service plug is correctly connected to the airplane. If the plug is accidentally connected backwards, no power will flow to the airplane's electrical system, thereby preventing any damage to electrical equipment.

The battery and external power circuits have been designed to completely eliminate the need to "jumper" across the battery contactor to close it for charging a completely "dead" battery. A special fused circuit in the external power system supplies the needed "jumper" across the contacts so that with a "dead" battery and an external power source applied, turning the master switch "ON" will close the battery contactor.

## STATIC PRESSURE ALTERNATE SOURCE VALVE.

A static pressure alternate source valve may be installed in the static system for use when the external static source is malfunctioning.

If erroneous instrument readings are suspected due to water or ice in the static pressure lines, the static pressure alternate source valve should be opened, thereby supplying static pressure from the cabin. Cabin pressures will vary, however, with open cabin ventilators or windows. The most adverse combinations will result in airspeed and altimeter variations of no more than 2 MPH and 15 feet, respectively.

## RADIO SELECTOR SWITCHES

### RADIO SELECTOR SWITCH OPERATION.

Operation of the radio equipment is normal as covered in the respective radio manuals. When more than one radio is installed, an audio switching system is necessary. The operation of this switching system is described below.




Figure 6-1.

## TRANSMITTER SELECTOR SWITCH.

The transmitter selector switch, labeled "TRANS," has two positions. When two transmitters are installed, it is necessary to switch the microphone to the radio unit the pilot desires to use for transmission. This is accomplished by placing the transmitter selector switch in the position corresponding to the radio unit which is to be used. The up position selects the upper transmitter and the down position selects the lower transmitter.

The installation of Cessna radio equipment provides certain audio back-up capabilities and transmitter selector switch functions that the pilot should be familiar with. When the transmitter selector switch is placed in position 1 or 2, the audio amplifier of the corresponding transmitter is utilized to provide the speaker audio for all radios. If the audio amplifier in the selected transceiver fails, as evidenced by loss of speaker audio for all radios, place the transmitter selector switch in the other transceiver position. Since an audio amplifier is not utilized for headphones, a malfunctioning amplifier will not affect headphone operation.

## SPEAKER PHONE SWITCHES.

The speaker-phone switches determine whether the output of the receiver in use is fed to the headphones or through the audio amplifier to the speaker. Place the switch for the desired receiving system either in the up position for speaker operation or in the down position for headphones.

## AUTOPILOT-OMNI SWITCH.

When a Nav-O-Matic autopilot is installed with two compatible omni receivers, an autopilot-omni switch is utilized. This switch selects the omni receiver to be used for the omni course sensing function of the autopilot. The up position selects the upper omni receiver in the radio panel stack and the down position selects the lower omni receiver.

## TRUE AIRSPEED INDICATOR

A true airspeed indicator is available to replace the standard airspeed indicator in your airplane. The true airspeed indicator has a calibrated rotatable ring which works in conjunction with the airspeed indicator dial in a manner similar to the operation of a flight computer.

TO OBTAIN TRUE AIRSPEED, rotate ring until pressure altitude is aligned with outside air temperature in degrees Fahrenheit. Then read true airspeed on rotatable ring opposite airspeed needle.

### NOTE

Pressure altitude should not be confused with indicated altitude. To obtain pressure altitude, set barometric scale on altimeter to "29.92" and read pressure altitude on altimeter. Be sure to return altimeter barometric scale to original barometric setting after pressure altitude has been obtained.

## FUEL TANK QUICK-DRAIN VALVE KIT

Two fuel tank quick-drain valves and a fuel sampler cup are available as a kit to facilitate daily draining and inspection of fuel in the main tanks for the presence of water and sediment. The valves replace existing fuel tank drain plugs located at the lower inboard area of the wing. The fuel sampler cup, which may be stowed in the map compartment, is used to drain the valves. The sampler cup has a probe in the center of the cup. When the probe is inserted into the hole in the bottom of the drain valve and pushed upward, fuel flows into the cup to facilitate visual inspection of the fuel. As the cup is removed, the drain valve seats, stopping the flow of fuel.

## WING LEVELER

A wing leveler may be installed to augment the lateral stability of the airplane. The system uses the Turn Coordinator for roll and yaw sensing. Vacuum pressure, from the engine-driven vacuum pump, is routed from the Turn Coordinator to cylinder-piston servo units attached to the aileron control system. As the airplane deviates from a wing level attitude, vacuum pressure in the servo units is increased or relieved as needed to actuate the ailerons to oppose the deviations.

A separately mounted push-pull control knob, labeled "WING LVLR," is provided on the left side of the instrument panel to turn the system on and off. A "ROLL TRIM" control knob on the Turn Coordinator is used for manual roll trim control to compensate for asymmetrical loading of fuel and passengers, and to optimize system performance in climb, cruise and let-down.

### OPERATING CHECK LIST

#### TAKE-OFF.

- (1) "WING LVLR" Control Knob -- Check in off position (full in).

#### CLIMB.

- (1) Adjust elevator trim for climb.
- (2) "WING LVLR" Control Knob -- Pull control knob "ON."
- (3) "ROLL TRIM" Control Knob -- Adjust for wings level attitude.

#### CRUISE.

- (1) Adjust power and elevator trim for level flight.
- (2) "ROLL TRIM" Control Knob -- Adjust as desired.

#### DESCENT.

- (1) Adjust power and elevator trim for desired speed and rate of descent.
- (2) "ROLL TRIM" Control Knob -- Adjust as desired.

#### LANDING.

- (1) Before landing, push "WING LVLR" control knob full in to the off position.

### EMERGENCY PROCEDURES

If a malfunction should occur, the system is easily overpowered with pressure on the control wheel. The system should then be turned off. In the event of partial or complete vacuum failure, the wing leveler will automatically become inoperative. However, the Turn Coordinator used with the wing leveler system will not be affected by loss of vacuum since it is designed with a "back-up" system enabling it to operate from either vacuum or electrical power in the event of failure of one of these sources.

### OPERATING NOTES

(1) The wing leveler system may be overpowered at any time without damage or wear. However, for extended periods of maneuvering it may be desirable to turn the system off.

(2) It is recommended that the system not be engaged during take-off and landing. Although the system can be easily overpowered, servo forces could significantly alter the manual "feel" of the aileron control, especially should a malfunction occur.



## CARBURETOR AIR TEMPERATURE GAGE

A carburetor air temperature gage may be installed in the airplane to help detect carburetor icing conditions. The gage is marked with a yellow arc between  $-15^{\circ}$  and  $+5^{\circ}\text{C}$ . The yellow arc indicates the carburetor temperature range where carburetor icing can occur; a placard on the gage reads "KEEP NEEDLE OUT OF YELLOW ARC DURING POSSIBLE ICING CONDITIONS."

Visible moisture or high humidity can cause carburetor ice formation, especially in idle or low power conditions. Under cruising conditions, the formation of ice is usually slow, providing time to detect the loss of RPM caused by the ice. Carburetor icing during take-off is rare since the full-open throttle condition is less susceptible to ice obstruction.

If the carburetor air temperature gage needle moves into the yellow arc during potential carburetor icing conditions, or there is an unexplained drop in RPM, apply full carburetor heat. Upon regaining the original RPM (with heat off), determine by trial and error the minimum amount of carburetor heat required for ice-free operation.

### NOTE

Carburetor heat should not be applied during take-off unless absolutely necessary to obtain smooth engine acceleration (usually in sub-zero temperatures).

## ALPHABETICAL INDEX

### A

After Landing, 1-4  
Air Filter, Carburetor, 4-8  
Aircraft,  
    before entering, 1-1  
    file, 406  
    ground handling, 4-1  
    inspection service-periods, 4-4  
    lubrication and servicing,  
        4-7, 4-8  
    mooring, 4-1  
    registration number, 1-6  
    securing, 1-4  
Airspeed Correction Table, 5-2  
Airspeed Indicator Markings, 3-3  
Airspeed Indicator, True, 6-5  
Airspeed Limitations, 3-2  
Alternator, 2-4  
Alternator Field Circuit Breaker,  
    2-3, 2-4  
Aluminum Surfaces, 4-3  
Ammeter, 1-6, 2-3, 2-4  
Authorized Operations, 3-1  
Autopilot Control Unit, 1-6

### B

Baggage, Weight, inside front cover  
Balked Landing, 1-4, 2-12  
Battery, 2-4, 4-8  
Battery Contactor, 2-4  
Beacon, Flashing, 2-5  
Before Entering Airplane, 1-1  
Before Landing, 1-4  
Before Starting Engine, 1-1  
Before Take-Off, 1-2, 2-8  
    magneto check, 2-8

    warm-up, 2-8  
Brake Master Cylinders, 4-8

### C

Cabin Air and Heat Controls, 1-6  
Cabin Heating, Ventilating and  
    Ventilating System, 2-5  
Capacity,  
    fuel, inside covers, 2-1  
    oil, inside covers  
Carburetor, 2-2  
    air filter, 4-8  
    air heat control, 1-6  
    air temperature gage, 1-6, 3-4,  
        6-8  
Care,  
    exterior, 4-2, 4-3  
    interior, 4-4  
    propeller, 4-3  
Center of Gravity Moment  
    Envelope, 3-6  
Check, Magneto, 2-8  
Cigar Lighter, 1-6  
Circuit Breakers and Fuses, 1-6,  
    2-3, 2-4  
Climb, 1-3, 2-10  
    data, 2-10, 5-3  
    maximum performance, 1-3  
    normal, 1-3  
    speeds, 1-3, 2-10  
Clock, 2-4  
Cold Weather Equipment, 6-1  
    ground service receptacle, 2-4,  
        6-2  
    static pressure alternate source  
        valve, 6-2  
    winterization kit, 6-1





Cold Weather Operation, 2-13  
flight operations, 2-14  
starting, 2-13  
Control Wheel Map Light, 2-5  
Compass, Magnetic, 1-6  
Compass Correction Card, 1-6  
Correction Table, Airspeed, 5-2  
Crosswind Landing, 2-12  
Crosswind Take-Offs, 2-9  
Cruise Performance, 2-10, 5-4  
Cruise Performance, Optimum,  
2-11  
Cruising, 1-3, 2-10, 5-4

## D

Data,  
climb, 2-10, 5-3  
landing, 5-5  
take-off, 5-3  
Diagram,  
electrical system, 2-4  
exterior inspection, iv  
fuel system, 2-2  
principal dimensions, ii  
taxiing, 2-7  
Dimensions, Principal, ii  
Dipstick, Oil, 4-7  
Drain Plug, Fuel Line, 4-7, 4-8  
Drain Plugs, Fuel Tank, 4-7

## E

Electrical System, 2-3  
alternator, 2-4  
ammeter, 1-6, 2-3, 2-4  
battery, 2-4, 4-8  
battery contactor, 2-4  
circuit breakers and fuses,  
1-6, 2-3, 2-4

Index-2

clock, 2-4  
control wheel map light, 2-4,  
2-5  
flashing beacon, 2-5  
ground service plug receptacle,  
2-4, 6-4  
ignition switch, 1-6, 2-4  
landing lights, 2-3  
magnetos, 2-4  
master switch, 1-6, 2-4  
regulator, 2-4  
reverse polarity contactor, 2-4,  
6-2  
schematic, 2-4  
split bus contactor, 2-4  
starter, 2-4  
starter contactor, 2-4  
switches, 1-6  
Elevator Trim Control Wheel, 1-6  
Empty Weight, inside front cover  
Engine, inside front cover  
before starting, 1-1  
instrument markings, 3-3  
oil sump, oil cooler and oil  
filter, 4-8  
operation limitations, 3-3  
primer, 2-2  
spark plugs, 4-8  
starting, 1-2, 2-5, 2-13  
Envelope, Center of Gravity Moment,  
3-6  
Equipment, Cold Weather, 6-1  
Exterior Care, 4-2, 4-3  
Exterior Inspection Diagram, iv

## F

File, Aircraft, 4-6  
Flap Switch, Wing, 1-6  
Flashing Beacon, 2-5  
Flight Hour Recorder, 2-4

Flight Instrument Group, 1-6  
Fuel and Oil Gages, 1-6, 3-3  
Fuel Specification and Grade,  
inside back cover  
Fuel System, 2-1  
capacity, inside covers  
carburetor, 2-2  
carburetor air temperature  
gage, 1-6, 3-4, 6-8  
fuel line drain plug, 4-7, 4-8  
fuel tanks (long range), 6-1  
fuel tanks (standard), 2-1, 2-2  
fuel tank sump drains, 4-7,  
4-8  
fuel tank quick-drain valve kit,  
6-5  
mixture control knob, 1-6, 2-2  
primer, 1-6, 2-2  
schematic, 2-2  
selector valve, 2-1, 2-2  
strainer, 2-2, 4-8  
tank fillers, 4-7  
throttle, 1-6, 2-2  
Fuses and Circuit Breakers, 1-6,  
2-3, 2-4

## G

Glide, Maximum, 5-6  
Gross Weight, inside front cover  
Ground Handling, 4-1  
Ground Service Receptacle, 2-4,  
6-2

## H

Handling Airplane on Ground, 4-1  
Heating, Ventilating and  
Defrosting System, Cabin, 2-5  
control knobs, 1-6  
Hot Weather Operation, 2-15  
Hydraulic Fluid Specification,  
inside back cover

Ignition/Starter Switch, 1-6, 2-4  
Inspection Diagram, Exterior, iv  
Inspection Service, Periods, 4-4  
Instrument Markings,  
air speed, 3-3  
engine, 3-3  
Instrument Panel, 1-6  
Instrument Space, 1-6  
Interior Care, 4-4

## L

Landing, inside front cover, 1-4,  
2-12  
after, 1-4  
balked, 1-4, 2-12  
before, 1-4  
crosswind, 2-12  
data, 5-5  
lights, 2-3  
normal, 1-4, 2-12  
short field, 2-12  
Let-Down, 1-3  
Light,  
flashing beacon, 2-5  
landing, 2-3  
Limitations, Airspeed, 3-2  
Limitations, Engine Operation, 3-3  
Loading Graph, 3-5  
Loading Problem, Sample, 3-4  
Long Range Fuel Tanks, 6-1  
Lubrication and Servicing  
Procedures, 4-7

## M

Magnetic Compass, 1-6  
Magneto Check, 2-8  
Magnetos, 2-4  
Maneuvers, Normal Category, 3-1

Index-3



Maneuvers, Utility Category, 3-2  
Map Compartment, 1-6  
Map Light, Control Wheel, 2-5  
Marker Beacon Indicator Lights  
and Switches, 1-6  
Markings, Instrument,  
airspeed, 3-3  
engine, 3-3  
Master Cylinders, Brake, 4-8  
Master Switch, 1-6, 2-4  
Maximum Glide, 5-6  
Maximum Performance Climb, 1-3  
Maximum Performance Take-Off,  
1-2  
Maximum Rate-of-Climb Data, 5-3  
Microphone, 1-6  
Mirror, Rear View, 1-6  
Mixture Control Knob, 1-6, 2-2  
Moment Envelope, Center of  
Gravity, 3-6  
Mooring Your Airplane, 4-1

## N

Normal Category, Maneuvers, 3-1  
Normal Climb, 1-3  
Normal Landing, 1-4, 2-12  
Normal Take-Off, 1-2  
Nose Gear,  
shock strut, inside back cover,  
4-9  
torque links, 4-8

## O

Oil and Fuel Gages, 1-6  
Oil Pressure Switch, 2-4  
Oil Specification and Grade, inside  
back cover  
Oil System,  
capacity, inside covers  
filter, 4-8

Index-4

oil filler and dipstick, 4-7  
oil sump, oil cooler and oil  
filter, 4-8  
pressure gage, 3-3  
temperature gage, 3-3  
Operating Limitations, Engine, 3-3  
Operation, Cold Weather, 2-13  
starting, 2-13  
flight operations, 2-14  
Operation, Hot Weather, 2-15  
Operations Authorized, 3-1  
Optimum Cruise Performance, 2-11  
Owner Follow-Up System, 4-10

## P

Painted Surfaces, 4-2  
Parking Brake Handle, 1-6  
Phone Jack, 1-6  
Power Loading, inside front cover  
Primer, Engine, 1-6, 2-2  
Principal Dimensions, ii  
Propeller, inside front cover  
care, 4-3

## R

Radio, 1-6  
Radio Selector Switches, 1-6, 6-3  
autopilot-omni switch, 6-3, 6-4  
operation, 6-3  
speaker-phone switches, 6-3,  
6-4  
transmitter selector switch,  
6-3, 6-4  
Range, inside front cover  
Range and Cruise Performance,  
5-4  
Rate of Climb, inside front cover,  
5-3  
Rear View Mirror, 1-6  
Receptacle, Ground Service, 2-4,  
6-2

Registration Number, 1-6  
Regulator, Voltage, 2-4  
Reverse Polarity Contactor, 2-4,  
6-2

## S

Sample Loading Problem, 3-4  
Secure Aircraft, 1-4  
Selector Valve, Fuel, 2-2  
Service Ceiling, inside front cover  
Servicing Intervals Check List, 4-8  
Servicing and Lubrication  
Procedures, 4-7  
Servicing Requirements Table,  
inside back cover  
Shimmy Dampener, 4-8  
Shock Strut, Nose Gear, 4-9, inside  
back cover  
Short Field Landing, 2-12  
Spark Plugs, 4-8  
Specification and Grade,  
fuel, inside back cover  
hydraulic fluid, inside back  
cover  
oil, inside back cover  
Specifications - Performance,  
inside front cover  
Speed, inside front cover  
Speeds, Climb, 1-3, 2-10, 5-3  
Split Bus Contactor, 2-4  
Stalling Speeds Chart, 5-2  
Stalls, 2-11  
Starter, 2-4  
Starter Contactor, 2-4  
Starter/Ignition Switch, 1-8  
Starting Engine, 1-2, 2-5, 2-13  
Static Pressure Alternate Source  
Valve, 1-6, 6-2  
Strainer, Fuel, 2-2, 4-7, 4-8  
Suction Gage, 1-6  
Suction Relief Valve Inlet Screen,  
4-8

Surfaces,  
aluminum, 4-2  
painted, 4-2  
System,  
cabin heating/ventilation, 2-5  
electrical, 2-3  
fuel, 2-1  
owner follow-up, 4-10

## T

Table of Contents, iii  
Tachometer, 1-6, 3-3  
Take-Off, inside front cover, 1-2,  
2-8  
before, 1-2, 2-8  
crosswind, 2-9  
data, 5-3  
maximum performance, 1-2  
normal, 1-2  
performance charts, 2-9  
power check, 2-8  
wing flap settings, 2-9  
Taxiing, 2-6  
diagram, 2-7  
Throttle, 1-6, 2-2  
Tire Pressures, inside back cover  
Torque Links, Nose Gear, 4-8  
True Airspeed Indicator, 6-5

## U

Utility Category, Maneuvers, 3-2

## V

Vacuum System Air Filter, 4-9  
Vacuum System Oil Separator, 4-8  
Valve, Fuel Selector, 2-2  
Voltage Regulator, 2-4

Index-5



# W

Weight,  
  baggage, inside front cover  
  empty, inside front cover  
  gross, inside front cover  
Weight and Balance, 3-4  
  loading graph, 3-5  
  moment envelope, 3-6  
  sample loading problem, 3-4

Wheel Bearings, 4-9  
Windshield and Windows, 4-2  
Wing Flap Position Indicator, 1-6  
Wing Flap Switch, 1-6  
Wing Leveler, 6-6  
  emergency procedures, 6-7  
  operating check list, 6-6  
  operating notes, 6-7  
Wing Loading, inside front cover  
Winterization Kit, 6-1



AIRCRAFT REGISTRATION

G-AZLV

Supplement No.

AIRWORTHINESS NOTICE NO.88

A flashing warning light is fitted which will illuminate if the generator / alternator fails and the battery supplies power to the bus bar .

Before engine start

Check low volts warning - on

After engine start

Check low volts warning - off

If warning illuminates during flight -

Reduce electrical load

Battery duration approx . 40..... mins.

Land as soon as possible .

NOTE: Warning may illuminate with low engine rpm  
Check it goes out when rpm is increased

Raised by AIR-TECH Auth. 329837K....  
Sig. *[Signature]*  
Date 21-5-2008..

T  
(  
b  
h  
j  
t  
b  
r  
b  
n  
s  
  
T  
O  
M  
O  
N  
T  
H  
I  
N

CIVIL AVIATION AUTHORITY  
ADDITIONAL LIMITATIONS AND INFORMATION FOR  
UNITED KINGDOM CERTIFICATION

CAA Supplement 1 Issue 1 to the Cessna 172K 1969  
Owner's Manual D625-13-RPC-400-3/85

Cessna  
Model 172K

Constructor's  
Serial No 172-57908

Registration  
Mark G-AZLV



The limitations and information contained herein either supplement or, in the case of conflict, override those in the Owner's Manual.

When the aeroplane is flown for the purpose of public transport, the performance information contained in the Owner's Manual, and in any relevant supplement or change sheet shall be used in assessing the ability of the aeroplane to comply with the requirements of the relevant Air Navigation (General) Regulation.

It is recommended that this same information is used by the commander before every flight, regardless of purpose, to satisfy himself that the aeroplane can take-off, carry out the flight and land safely in the conditions expected, so as to comply with the pre-flight action by the commander of an aircraft required by the Air Navigation Order.

CAA Supplement 1  
Issue 1

Page 1 of 6

CAA Approved  
6 December 1989

AIRCRAFT REGISTRATION

G-AZLV

Supplement No.

AIR WORTHINESS NOTICE NO.88

A flashing warning light is fitted which will illuminate if the generator / alternator fails and the battery supplies power to the bus bar .

Before engine start

Check low volts warning - on

After engine start

Check low volts warning - off

If warning illuminates during flight -

Reduce electrical load

Battery duration approx . 40..... mins.

Land as soon as possible .

NOTE: Warning may illuminate with low engine rpm  
Check it goes out when rpm is increased

Raised by AIR-TECH    Auth. 329837K....  
                                  Sig. *[Signature]*  
                                  Date 21-5-2008..

DESCRIPTION AND OPERATING DETAILS/  
NORMAL PROCEDURES

1. Starting Engine. A starter energised warning light comes on to indicate that the starter motor relay is energised closed when the starter is operated. If the light stays on after the starter button has been released, the starter motor relay is being held closed by a malfunction and the starter motor will continue to rotate until its electrical supply is terminated, in which case switch off internal and external electrical power, complete the engine shut-down drills and investigate the cause.
2. Carburetor Icing. If conditions require the use of carburetor heat, use full heat continuously or intermittently as required, and lean the mixture slightly for smoothest engine operation.

LIMITATIONS

1. This type of aeroplane is eligible for certification in the Transport Category (Passenger).

However, this particular aeroplane may be restricted to another Category and to some particular use. This will be stated in the Certificate of Airworthiness.

I  
P  
j  
t  
k  
r  
e  
s  
  
T  
C  
M  
C  
N  
T  
Q  
T  
H

ADDITIONAL LIMITATIONS AND INFORMATION FOR  
UNITED KINGDOM CERTIFICATION

2. When operated in the Transport Category (Passenger), the aeroplane is classified in Performance Group E.
3. The minimum crew is one pilot.
4. The total number of persons carried including crew shall not exceed four nor the number of seats approved for use during take-off and landing.

If a child's seat is fitted and equipped with safety belt(s) the occupant(s) of this seat up to and including a total weight of 120 lb may be added to the total.

Children under the age of two years carried in the arms of passengers need not be included in the total.

5. Kinds of Operation Limits. For flight by night or IFR refer to the air navigation legislation for equipment required.
6. Flight into known or forecast icing conditions is prohibited.

ADDITIONAL LIMITATIONS AND INFORMATION FOR  
UNITED KINGDOM CERTIFICATION

2. When operated in the Transport Category (Passenger), the aeroplane is classified in Performance Group E.
3. The minimum crew is one pilot.
4. The total number of persons carried including crew shall not exceed four nor the number of seats approved for use during take-off and landing.

If a child's seat is fitted and equipped with safety belt(s) the occupant(s) of this seat up to and including a total weight of 120 lb may be added to the total.

Children under the age of two years carried in the arms of passengers need not be included in the total.

5. Kinds of Operation Limits. For flight by night or IFR refer to the air navigation legislation for equipment required.
6. Flight into known or forecast icing conditions is prohibited.

ADDITIONAL LIMITATIONS AND INFORMATION FOR  
UNITED KINGDOM CERTIFICATION

7. No aerobatic manoeuvres are permitted other than those associated with the Utility Category as listed in the Owner's Manual. The limitations for the Utility Category given in the Manual shall be complied with.

**EMERGENCY PROCEDURES**

1. Engine Starting During Flight. If the starter energised warning light stays on after the starter has been operated, the starter motor is continuing to rotate and is therefore still engaged. Land as soon as practicable. After landing, isolate the batteries as quickly as possible then carry out the engine shut-down drills.
2. Complete Electrical Failure. This failure causes the loss of all radio, the turn co-ordinator, the fuel quantity indicators and the wing flaps. Turn the master switch to OFF and land as soon as possible.



ADDITIONAL LIMITATIONS AND INFORMATION FOR  
UNITED KINGDOM CERTIFICATION

PERFORMANCE

1. When operating on short dry grass the hard-surface runway take-off distance to a height of 50ft and the landing distance from a height of 50ft must each be increased by 20%.

When operating on short wet grass on a firm subsoil the hard-surface runway take-off distance to a height of 50ft must be increased by 25%, and the landing distance from a height of 50ft must be increased by 30%.

In all cases the effect on the ground run/roll will be greater.

2. Flapless landing. For a flapless landing use an approach speed of 72 mph IAS and increase the scheduled landing distance by 10%.

ADDITIONAL LIMITATIONS AND INFORMATION FOR  
UNITED KINGDOM CERTIFICATION

SUPPLEMENTS

1. Ground Service Plug Receptacle.  
Do not recharge the battery in position  
on the aircraft.
  
2. Wing Leveler.  
The minimum permissible height for wing  
leveler engagement and for flight with it  
engaged is 300ft above the terrain.

To be inserted at the back of the Owner's Manual  
and the CAA revisions record sheet amended  
accordingly.

## SERVICING REQUIREMENTS

---

---

### FUEL:

AVIATION GRADE -- 80/87 MINIMUM GRADE  
CAPACITY EACH STANDARD TANK -- 21 GALLONS  
CAPACITY EACH LONG RANGE TANK -- 26 GALLONS

### ENGINE OIL:

AVIATION GRADE -- SAE 50 ABOVE 60°F  
SAE 10W30 or SAE 30 BETWEEN 0° and 70°F  
SAE 10W30 OR SAE 20 BELOW 10°F

(MULTI-VISCOSITY OIL WITH A RANGE OF SAE 10W30 IS RECOMMENDED FOR IMPROVED STARTING AND LUBRICATION DURING WARM-UP IN COLD WEATHER. DETERGENT OR DISPERSANT OIL, CONFORMING TO LYCOMING SPECIFICATION NO. 301E, MUST BE USED.)

CAPACITY OF ENGINE SUMP -- 8 QUARTS

(DO NOT OPERATE ON LESS THAN 6 QUARTS. TO MINIMIZE LOSS OF OIL THROUGH BREATHER, FILL TO 7 QUART LEVEL FOR NORMAL FLIGHTS OF LESS THAN 3 HOURS. FOR EXTENDED FLIGHT, FILL TO 8 QUARTS. IF OPTIONAL OIL FILTER IS INSTALLED, ONE ADDITIONAL QUART IS REQUIRED WHEN THE FILTER ELEMENT IS CHANGED.)

### HYDRAULIC FLUID:

MIL-H-5606 HYDRAULIC FLUID

### TIRE PRESSURES:

NOSE WHEEL ----- 26 PSI ON 5.00 X 5 TIRE  
26 PSI ON 6.00 X 6 TIRE  
MAIN WHEELS ----- 24 PSI ON 6.00 X 6 TIRES

### NOSE GEAR SHOCK STRUT:

KEEP FILLED WITH FLUID AND INFLATED TO 45 PSI.

---



"TAKE YOUR CESSNA HOME  
FOR SERVICE AT THE SIGN  
OF THE CESSNA SHIELD".

CESSNA AIRCRAFT COMPANY



WICHITA, KANSAS